


SWITCHGEAR CUBICLE DESIGNATION
FOR LOW VOLTAGE DOUBLE-ENDED
SWITCHGEAR RATED 3200A OR SMALLER

GENERAL NOTES:

- 1. PROVIDE REVENUE ACCURACY CTS AND PTS AS REQUIRED.
- 2. CUBICLE SECTIONS CAN ACCOMMODATE UP TO 3200A BREAKER.
IF BREAKERS ARE TOO LARGE TO FIT IN ONE CUBICLE, USE
CUBICLE NUMBERING SYSTEM SHOWN ON DRAWING 16430.2

CUBICLE (1A)	CUBICLE (2A)	CUBICLE (3A)	CUBICLE (4A)
CUBICLE (1B)	CUBICLE (2B)	CUBICLE (3B)	CUBICLE (4B)
CUBICLE (1C)	CUBICLE (2C)	CUBICLE (3C)	CUBICLE (4C)
CUBICLE (1D)	CUBICLE (2D)	CUBICLE (3D)	CUBICLE (4D)



DESIGNED BY	DATE	DETAIL:		
MT	11/07/12	STA, F&I STANDARD DETAILS LV SWITCHGEAR CUBE LAYOUT 3200A AND LARGER		
DRAWN BY	DATE			
DCD	11/07/12			
CHECKED BY	DATE			
APPROVED BY	DATE	REVISION:	DESCRIPTION:	STD:
		0		262300
				02