



ACS DOOR TYPES/SCHEDULES & CAT6 CABLES				
	TYPE 1	TYPE 2	TYPE 3	TYPE 4
Number of BR	2	1	1	1
Number of CR	0	1	0	0
Number of CAM	2	2	1	1
Number of IC	2	2	2	1
Total Devices	6	5	4	3
Home Run CAT6	6	5	4	3
Extra CAT6	4	4	3	2
Total CAT6	10	9	7	5

BR: BIOMETRIC CARD READER (MA SIGMA)
CR: CARD READER (HID) WITH PIN PAD OR WITHOUT PIN PAN
CAM: IP CAMERA
IC: IP INTERCOM

NOTES:

1. 10X10 enclosure to be lockable with 270 lockcore.
2. 10x10 enclosure & ITB to be connected via a 1.5" conduit.
3. ACS IP devices (Camera & Intercom) to be home run through 10x10 enclosure adjacent to ITB.
4. 10x10 enclosure can be right, left, top or bottom of ITB.
5. 10x10 enclosure to be NEMA rated depending on where it is installed.
6. If type 4 door is a EQ./Comm Room door, 10x10 enclosure is not required.

TITLE		CAT6 CABLES LAYOUT FOR ACS			DATE
SIZE		FSCM NO.		DWG NO.	REV
11x17				ACS- BLOCK-2	0
DESIGNED BY		DRAWN BY		FILE NAME	SHEET
N. SAHOTA		J. Lee		ACS_Block2.dwg	1/1